

# MMA Technical Standards Board/ AMEI MIDI Committee

## Scalable Polyphony MIDI Specification (RP-034)

### Errata

#### For Version 1.0a; May , 2002

1. Change the MIP message example in section 2.2.1 on page 6, lines 3-4

From:

```
F0 7F 7F 09 04 00 04 09 09 01 0A 02 0C 03 0C 0A 10 04 11 08 14 05 1A 07 1A  
06 1A 0B 1A 0C 1A 0D 1A 0E 1A 0F 1A F7
```

To:

```
F0 7F 7F 0B 01 00 04 09 09 01 0A 02 0C 03 0C 0A 10 04 11 08 14 05 1A 07 1A  
06 1A 0B 1A 0C 1A 0D 1A 0E 1A 0F 1A F7
```

2. Change the second bullet in the definition of incorrect MIP messages in section 3.1.3 on page 9, line 34 From:

- Any of the 16 MIDI Channels is not presented exactly once

To:

- Any MIDI channel is presented more than once

3. Increment the version number and publication date.
4. Update reference in Profile document, and change publication date.
5. Update reference to Profile document.

#### Added For Version 1.0b; November 2004

6. Change the first sentence in section 3.1.2 on page 9, line 22 From:

- All SP-MIDI content should begin by sending an appropriate device Reset Message.

To:

- Playback of all SP-MIDI SMF content should be initiated by sending the synthesizer an appropriate device Reset Message before starting the file.